

REV.	DESCRIPTION	DATE
A	RELEASE	Jul. 05, 2002
B	SPEC. MODIFY	Jul. 08, 2002
C	DRAW MODIFY	Jul. 17, 2002
D	DRAW MODIFY	Mar. 31, 2005
E	DRAW MODIFY	Nov. 17, 2005
F	DRAW MODIFY	May. 20, 2008
G	DRAW MODIFY	Jun. 20, 2011

MATERIALS

- HOUSING : L.C.P (UL 94V-0), BLACK.
- TERMINAL : SILVER PLATING.
#1, TI-CU.
#2, #3 BRASS.
- INNER PIN : FREE CUTTING BRASS, NICKEL PLATING.

SPECIFICATION

- CURRENT RATING : 3 AMP. MAX.
- DIELECTRIC WITHSTANDING VOLTAGE :
250V AC R.M.S. FOR ONE MINUTE.
- INSULATION RESISTANCE : 100M OHMS MIN.
AT 250V DC
- CONTACT RESISTANCE : 30m OHMS MAX.
- OPERATING TEMPERATURE : -25°C TO +85°C.
- DURABILITY : 5000 CYCLES.
- MATING FORCE : 0.2 ~ 2.0kgs.
- UNMATING FORCE : 0.2 ~ 2.0kgs.

PART NUMBER INFORMATION


15 - 02 03 * - R

SERIES CODE TYPE 03 ENVIRONMENTAL PROTECTION CODE (RoHS)

INNER PIN DIA. OPTIONS
7 : $\phi 1.30\text{mm}$
8 : $\phi 1.00\text{mm}$

RECOMMEND P.C.B LAYOUT
TOP VIEW

SCHEMATIC



TOLERANCE .0=±.30 .00=±.20 .000=±.XXX .0000=±. ANG.=±3°		DRAWER <i>BEN</i>	Astron WWW.ASTRON.COM.TW
UNITS : mm [inch]		CHECK <i>JING</i>	
SCALE NONE SIZE A4		APP'D <i>JANICE</i>	NAME DC POWER JACK P.C.B. MOUNT, SMT TYPE FEMALE
SHEET 1 OF 1		PRODUCT SPEC. 516-0008 C522-0204	DRAW NO. C15-0203X-R
		REV. G	08005

DATE CODE
YYMMDD
DAY
MONTH
YEAR

